



FLAT WEBBING SLING

FLAT WEBBING SLING



Specification:






RE-useable webbing slings manufactured in accordance with BS 3481 Pt.2 1983 F:S 7:1(re-useable), DIN-EN 1492-1 and the essential requirements of the European Machinery Directive.

Color coded and stripped for WLL(working load limit) identification. Manufactured from 100% high tenacity continuous filament polyester fibre. All webbing slings are individually numbered and are fully traceable. Every single webbing sling is labeled and certificated in accordance with the relevant standard together with information about safety use and maintenance.














Available:

Simplex, duplex & quadruplex ply standard slings, single and double endless slings, twin sling etc. In standard and long length up to 300mm width. With flat or becket (folded) eyes with or without re-inforcement. Label printed with customer logo on request.

Eye Types for Web sling

	I	Option 1: Flat eye
	I	Option 2: Reversed eye
	II	Option 3: Folded eye 1/2 width from 1 side
	II	Option 4: Folded eye 1/2 width from 2 sides
	III	Option 5: Folded eye 1/3 width




EUROPEAN STANDARD PARAMETER:

Color according to EN-1492-1	Width in mm (SF 7:1)	Working Load Limit (WLL in kgs)				
		Vertical	Choker	Basket Lifting		
				A=0-7°	A=7-45°	A=45-60°
						
M=1.0	M=0.8	M=2.0	M=1.4	M=1.0		
 Purple (4005)	30	1000	800	2000	1400	1000
 Green (6018)	60	2000	1600	4000	2800	2000
 Yellow (1018)	90	3000	2400	6000	4200	3000
 Gray (7001)	120	4000	3200	8000	5600	4000
 Red (3020)	150	5000	4000	10000	7000	5000
 Brown (8003)	180	6000	4800	12000	8400	6000
 Blue (5015)	240	8000	6400	16000	11200	8000
 Orange (2008)	300	10000	8000	20000	14000	10000



AMERICAN-STANDARD PARAMETER:

ASME Standard Eye-eye Flat Webbing Sling

PLY	Item No.	Width (inch)	Color	Rated Capacity (LBS)			Eye Length (inch)
				 Vertical	 Choker	 Basket	
One Play	FS-A5SEE1600LBS	1"	Yellow	1600	1280	3200	10
	FS-A5SEE3200LBS	2"	Yellow	3200	2500	6400	12
	FS-A5SEE3800LBS	3"	Yellow	4800	3800	9600	14
	FS-A5SEE5000LBS	4"	Yellow	6400	5000	12800	14
	FS-A5SEE9600LBS	6"	Yellow	9600	7700	19200	16
	FS-A5SEE12800LBS	8"	Yellow	12800	10200	25600	20
	FS-A5SEE16000LBS	10"	Yellow	16000	12800	32000	24
	FS-A5SEE19200LBS	12"	Yellow	19200	15400	38400	24
Two Play	FS-A5DEE3200LBS	1"	Yellow	3200	2500	6200	10
	FS-A5DEE6400LBS	2"	Yellow	6400	5000	12400	12
	FS-A5DEE8800LBS	3"	Yellow	8800	7040	17600	14
	FS-A5DEE12000LBS	4"	Yellow	12000	9600	24000	14
	FS-A5DEE16500LBS	6"	Yellow	16500	13200	33000	16
	FS-A5DEE19200LBS	8"	Yellow	19200	15400	38400	20
	FS-A5DEE17900LBS	10"	Yellow	22400	17900	44800	24
	FS-A5DEE21500LBS	12"	Yellow	26900	21500	53800	24

ROUND SLING



ROUND SLING

Specification:

Manufactured in accordance with BS 6668 Pt.2 1987, DIN-EN 1492-2 and essential requirements of European Machinery Directive. The load bearing core of a round sling is manufactured from 100% high tenacity continuous filament polyester fibre which is protected by an abrasion resistance tubular polyester webbing cover.



Color coded and striped for WLL(Working Load Limit) identification. All round slings are individually numbered and are fully traceable. Every single round sling is labeled and certificated in accordance with relevant standard together with information about safety use and maintenance.

Available:

In lengths up to 18 meter working(36m circumference). Capacity up to 20 ton WLL(Working Load Limit) per sling. Label printed with customer logo on request.



EUROPEAN STANDARD PARAMETER:

According to EN1492-2:2000 (SF=7:1)

Stock.No Color	WLL	SWL WLL (T) M CC					Double Multi-set SWL (T)			
				0-7°	7-45°	45-60°	<45°	<45°	45-60°	45-60°
1	0.8	2	1.4	1	1.4	1.12	1	0.8		
E7RS010	WLL 1T	1000	800	2000	1400	1000	2800	1120	1000	800
E7RS020	WLL 2T	2000	1600	4000	2800	2000	5600	2240	2000	1600
E7RS030	WLL 3T	3000	2400	6000	4200	3000	8400	3360	3000	2400
E7RS040	WLL 4T	4000	3200	8000	5600	4000	11200	4480	4000	3200
E7RS050	WLL 5T	5000	4000	10000	7000	5000	14000	5600	5000	4000
E7RS060	WLL 6T	6000	4800	12000	8400	6000	16800	6720	6000	4800
E7RS080	WLL 8T	8000	6400	16000	11200	8000	22400	8960	8000	6400
E7RS100	WLL 10T	10000	8000	20000	14000	10000	28000	11200	10000	8000
E7RS120	WLL 12T	12000	9600	24000	16800	12000	33600	13440	12000	9600



AMERICAN-STANDARD PARAMETER:

ASME standard Endless Round Sling







Stock. NoColor	Item No.	SleeveWidth (mm)	Working Load Limit (LBS)				Body diameter (inch)	Min. length (FT)
			Vertical	Choker	Basket 90°	Basket 45°		
Purple	RS-A5EN2600	44-45	2600	2100	5200	3600	0.63	3
Green	RS-A5EN5300	54-55	5300	4200	10600	7400	0.88	3
Yellow	RS-A5EN8400	63-64	8400	6700	16800	11800	1.13	3
Tan	RS-A5EN12000	68-70	12000	8500	21200	14000	1.13	3
Red	RS-A5EN13200	78-80	13200	10600	26400	18000	1.38	3
Orange	RS-A5EN17000	83-85	17000	13400	33600	23000	1.38	6
Blue	RS-A5EN21200	95-98	21200	17000	42400	29000	1.75	6
Orange	RS-A5EN26000	100-105	26000	20000	50000	35000	1.87	6
Grey	RS-A5EN31000	110-115	31000	24800	62000	43000	2.25	6
Orange	RS-A5EN40000	125-130	40000	32000	80000	56000	2.5	8
Brown	RS-A5EN54000	130-135	54000	42400	106000	74000	2.75	8
Olive	RS-A5EN68000	135-140	68000	52800	132000	93000	3.13	8
Black	RS-A5EN90000	145-150	90000	72000	180000	127000	3.63	8

AMERICAN-STANDARD PARAMETER:

ASME standard Eye to Eye Round Sling



Stock.No Color	Item No.	SleeveWidth (mm)	Working Load Limit (LBS)				Body diameter (inch)	Min. length (FT)
			 Vertical	 Choker	 Basket 90°	 Basket 45°		
Purple	RS-A5EE2600	44-45	2600	2100	5200	3600	0.63	3
Green	RS-A5EE5300	54-55	5300	4200	10600	7400	0.88	3
Yellow	RS-A5EE8400	63-64	8400	6700	16800	11800	1.13	3
Tan	RS-A5EE12000	68-70	12000	8500	21200	14000	1.13	3
Red	RS-A5EE13200	78-80	13200	10600	26400	18000	1.38	3
Orange	RS-A5EE17000	83-85	17000	13400	33600	23000	1.38	6
Blue	RS-A5EE21200	95-98	21200	17000	42400	29000	1.75	6
Orange	RS-A5EE26000	100-105	26000	20000	50000	35000	1.87	6
Grey	RS-A5EE31000	110-115	31000	24800	62000	43000	2.25	6
Orange	RS-A5EE40000	125-130	40000	32000	80000	56000	2.5	8
Brown	RS-A5EE54000	130-135	54000	42400	106000	74000	2.75	8
Olive	RS-A5EE68000	135-140	68000	52800	132000	93000	3.13	8
Black	RS-A5EE90000	145-150	90000	72000	180000	127000	3.63	8

